

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Serial No.:	10/540436	Confirmation No.:	1654
Applicant(s):	Dirk Nuber	Group Art Unit:	3653
Filed:	11/10/2005	Examiner:	
For:	METHOD AND APPARATUS FOR HEAT TREATMENT IN A FLUIDIZED BED	Customer No.:	27123

**REQUEST FOR REPUBLICATION**

**Via USPTO E-Filing**

Dear Sir:

Re-publication is requested to include the omitted inventors in view of the error which appears in the original publication (inventors omitted: Werner Stockhausen and Michael Stroder). For the convenience of the Patent and Trademark Office, attached is a photocopy of the original publication, on which the error has been highlighted, a copy of the executed declaration and the application transmittal as filed.

The Commissioner is hereby authorized to charge any additional fees which may be required by this paper, or credit any overpayment to Deposit Account No. 13-4500, Order No. 4791-4011.

Respectfully submitted,  
MORGAN & FINNEGAN, L.L.P.

Dated: March 1, 2007

By:

  
Bartholomew Verdrame  
Registration No. 28,483

**Correspondence Address:**

MORGAN & FINNEGAN, L.L.P.  
3 World Financial Center  
New York, NY 10281-2101  
(212) 415-8700 Telephone  
(212) 415-8701 Facsimile



(19) **United States**

(12) **Patent Application Publication** (10) Pub. No.: US 2006/0231466 A1  
 Number (43) Pub. Date: Oct. 19, 2006

Nuber

(43) Pub. Date:

**Oct. 19, 2006**

(54) METHOD AND APPARATUS FOR HEAT TREATMENT IN A FLUIDIZED BED

(52) U.S. CL. 209/11; 209/455; 208/128

(76) Inventor: Dirk Nuber, Oberursel (DE)

(57)

## ABSTRACT

**Correspondence Address:**  
**MORGAN & FINNEGAN, L.L.P.**  
**3 WORLD FINANCIAL CENTER**  
**NEW YORK, NY 10281-2101 (US)**

(21) Appl. No.: 10/540,436

(22) PCT Filed: Dec. 10, 2003

(86) PCT No.: PCT/EP03/13982

(30) Foreign Application Priority Data

Dec. 23, 2002 (DE) 10260741.9

### Publication Classification

(51)	Int. Cl.	
	B03B	9/06 (2006.01)
	C10G	9/36 (2006.01)

The present invention relates to a method for the heat treatment of fine-grained acids, in particular gypsum, in which the solids are heated to a temperature of 50 to 1000°C. In a fluidized bed reactor (1), and to a corresponding plant, to improve the energy utilization, it is proposed to introduce the hot gas or gas mixture from below through a preferably central gas supply tube (3) into a mixing chamber (21) of two reactor (1), the gas supply tube (3) being at least partly surrounded by a stationary annular fluidized bed (2) which is fluidized by supplying fluidizing gas, and to adjust the gas velocities of the first gas or gas mixture as well as of the fluidizing gas for the annular fluidized bed (2) such that the particle Froude numbers in the gas supply tube (3) are between 1 and 100, in the annular fluidized bed (2) between 0.02 and 2 and in the mixing chamber (21) between 0.5 and 30.

